

AQUA TEC[®] NF 2

Water based, CFC (chlorofluorocarbons) free, non-flammable spray adhesive

AQUA TEC NF 2 is a non-combustible, sprayable adhesive that does not contain CFCs as propellants. The main field of application is fabric fixation on printing tables, during the printing process, particularly when using flash-curing units for drying. In addition, it is suitable for adhering various materials such as paper, cardboard, textiles, glass and many plastics.

APPLICATION:

PROCESSING

Shake the Spray can briefly before each use.

Spray at a distance of approx. 20-30 cm.

At the start of work, spray the pallet well, as usual.

Spraying of AQUA TEC NF 2 on warmed up printing tables achieves a faster adherence.

The drying time depends on the adhesive layer and the ambient temperature. Only completely dried adhesive films can achieve optimal processing properties.

Over time, the adhesive layer may dull. It only takes a short spray to activate the adhesive layer again.

Note: The suitability of the adhesive, in conjunction with the various substrates, must be cleared by preliminary tests.

CLEANING

Wet glue can be removed with water. Dried adhesive can be completely removed from the printing pallet with PREGAN 1014 E.

PRODUCT DATA:

COLOUR

White, transparent after drying.

HEALTH HAZARDS/ ENVIRONMENTAL

Container is under pressure. Protect from sunlight & temperatures above 50 °C. Once empty, do not forcefully open or burn. Contains 20 mass percent flammable components. Keep out of the reach of children.

PROTECTION

Please follow further information given in the material safety data sheet.

STORAGE

1 year at 20–25°C in original spray can. Protect from frost/freezing