

KIWO® PowerSpray

Aerosol Contact Adhesive

KIWO PowerSpray is a spray-capable contact adhesive with high initial adhesion and temperature resistance. The main application area is the bonding of various materials such as plastics, metals, wood and wood fiber materials, leather, synthetic leather, textiles, spacer fabric, polyether-, polyester- and polyurethane foams and much more. Not suitable for styrofoam and soft PVC. The bonding reaches their final strength after approx. 24 hours.

Preparation

Shake can well prior to use.

Before applying adhesive, the surfaces to be bonded must be thoroughly cleaned. For bonding, the adhesive must be sprayed on both sides on the parts to be bonded. Spray distance approx. 15 - 25 cm. Strongly absorbent substrates may be sprayed twice. Before bonding, the adhesive should be ventilated for approx. 5 - 15 min. depending on the application strength and room temperature. The parts are then joined together.

After use, turn the can upside down and activate the valve until only gas is emitted.

Please note: The suitability of the adhesive in connection with the various substrates has to be checked by pre-trials.

Cleaning

MECOPLUS 4270 RE-L

Colour

Colourless, cloudy

Safety tips / Environmental protection

Pressurised container, therefore, protect from heating up to more than 50° C i.e. by sun rays). After use, do not open by force or burn the container. Do not spray on open flames or onto red hot objects. Gas is propellant free from CFC. Please check further tips in the safety data sheet.

Storage

1 year (at 20° to 25° C in the original can)

This data sheet is for your information. A legally binding assurance of the product's suitability for a specific purpose cannot be derived from it and no liability can be assumed for any potential damages that may occur. Liability for damages due to a slightly negligent breach of duty on our part or on the part of our legal representative or vicarious agent is excluded. Our liability for damages due to injury to life, body or health is not covered by this limitation of liability. Our products are subject to continuous production and quality control and leave our company in perfect condition.

This product is intended solely for industrial applications and not for use by the end consumer. We recommend to our customers to always test the product themselves since only in this way – also after production – can the freedom from certain substances and the suitability for a particular purpose be verified. The user has to test the product for suitability for the intended application. We reserve the right to modify product specifications. Tests that are not part of the specifications of the product mentioned above have not been carried out. All information applies only to the above-mentioned product obtained from Kissel + Wolf GmbH. It corresponds to our current state of knowledge, but is not a confirmation of a particular application and is not automatically replenished.

All information is valid for a maximum of 12 months from the date stated above (annexes may be provided with their own date). Any industrial property rights as well as existing laws and regulations are to be observed by the recipient of our product on his own responsibility. Intellectual property rights of third parties must be observed. Our terms and conditions of sale and delivery shall apply.