



MECOFLOCK® D 466 LE

Sprayable, one-component, dispersion-based flocking adhesive



Product benefits

- low overall emission
- free of Isocyanate
- water based
- approved according to DBL 5430 (Daimler-Benz delivery regulations)
- good resistance against condensation according to DIN 50017-KK
- optimized smell

MECOFLOCK® D 466 LE

MECOFLOCK D 466 LE is a one-component, dispersion-based flocking adhesive for spraying, to be used for the flocking of PS (Polystyrene), ABS (Acrylonitrile-Butadiene-Styrene-Terpolymers), SAN (Styrene-Acryl-Nitrile-Copolymers), wood, chip boards, many metals and other substrates.

LE stands for „Low Emission“ and shows the central advantage of the low overall emission. In addition, the flocking adhesive is approved according to DBL 5430 (Daimler-Benz delivery regulations).

Properties:

- base: watery acrylate dispersion
- colour: black
- viscosity: 5500 mPas*
- pot life: not applicable
- ph-value: 7,0 approx.
- storage: 12 months

* Brookfield RVT, spindle 4, 20 rpm, 20° C



Ask for a sample to be convinced by hands-on-tests!

Adhesives by KIWO®

Screen adhesives

- solvent-based
- UV-curing

Screen printable adhesives

- water-based
- solvent-based
- UV-curing

Special adhesives

- laminating adhesives
- spray adhesives
- flock adhesives
- printing blanket adhesives

KIWO
ONLINE

