

## KIWOFILLER® 405 Colourless

### Solvent resistant screenfiller

KIWOFILLER 405 Colourless used for retouching works and blocking-out of solvent resistant stencils. It is fast drying and forms an elastic, very solvent and abrasion resistant film. Excellent flowing and wetting properties. KIWOFILLER 405 Colourless remains water soluble and can therefore be removed from the mesh with cold or warm water without any residue.

**APPLICATION**                      Retouching:                      Apply KIWOFILLER 405 Colourless with a brush onto the areas to be retouched. When using fine meshes, it is also possible to use a coating trough.

For very precise retouch work with a thin brush, reduce KIWOFILLER 405 Colourless with approx. 10% of water.

Blocking-out:                      Apply KIWOFILLER 405 Colourless with a brush or coating trough.

**DRYING TIME**    Approx. 15 min. at 20°-25°C

**REDUCING/  
CLEANING**    Water

---

**COLOUR**    Colourless

**VISCOSITY**    Approx. 1500 mPas (Rheomat RM 180, MS 33, D = 100 s<sup>-1</sup>, 23°C)

**HEALTH HAZARDS/  
ENVIRONMENTAL  
PROTECTION**    In usual working dilution, KIWOFILLER 405 Colourless residue can be emptied into drains.

Please follow further information given in the material safety data sheets.

**STORAGE**    2 years (at 20 - 25°C and tightly closed original container)