Technical Information



Replaces the Technical Information 10.12.07

Update: 16.07.08

KIWOFILLER® 407 Red

Solvent resistant screenfiller

KIWOFILLER 407 Red is used for blocking-out and retouch works of solvent resistant stencils. It is fast drying and forms an elastic, very solvent and abrasion resistant film. It has excellent flowing and wetting properties. KIWOFILLER 407 Red remains water soluble and can therefore be removed from the mesh with cold or warm water without any residue.

APPLICATION Retouching: Apply KIWOFILLER 407 Red with a brush onto the areas to

be retouched. When using fine meshes, it is also possible

to use a coating trough.

For very precise retouch work with a thin brush, reduce

KIWOFILLER 407 Red with approx. 10% of water.

Blocking-out: Apply KIWOFILLER 407 Red with a brush or coating trough.

DRYING TIME Approx. 15 min. at 20°-25°C

REDUCING/ CLEANING Water

COLOUR Red

VISCOSITY Approx. 1500 mPas (Rheomat RM 180, MS 33, D = 100 s^{-1} , 23°C)

HEALTH HAZARDS/ ENVIRONMENTAL PROTECTION In usual working dilution, KIWOFILLER 407 Red residues can be emptied

into drains.

Please follow further information given in the material safety data sheets.

STORAGE 2 years (at 20 - 25°C and tightly closed original container)