

## KIWOSOLV® L 63

### Reducer and solvent cleaner for adhesives

KIWOSOLV L 63 can be used for reducing many adhesives. For details on quantities please refer to the Technical Information sheet of the respective adhesive. KIWOSOLV L 63 can also be used for removal of adhesive residues and as a brush cleaner.

#### APPLICATION

As reducer: Add the quantity of KIWOSOLV L 63 given in the Technical Information sheet of the adhesive and stir thoroughly, or add the solvent in small doses until the desired viscosity is reached.

As cleaner: Apply KIWOSOLV L 63 on a cloth and remove the adhesive residue. Repeat the cleaning process for stubborn contaminations.

Notice: Test compatibility of KIWOSOLV L 63 when working on plastic or lacquered surfaces or with lacquered tools.

---

|   |  |
|---|--|
| <b>COLOUR</b>   | Colourless   |
| <b>DENSITY</b>  | Approx. 0,80 g/cm <sup>3</sup>   |
| <b>FLASH POINT</b>                                      | Approx. -18°C  |
| <b>HEALTH HAZARDS/<br/>ENVIRONMENTAL<br/>PROTECTION</b> | Please follow further information given in the material safety data sheet. |
| <b>STORAGE</b>  | 3 years (at 20-25°C in original container)                                 |